



## DB0208 2 – 8 GHz 12-Way Power Divider/Combiner


### FEATURES

- ❖ Low VSWR
- ❖ High Isolation
- ❖ Small Package
- ❖ Light Weight



### SPECIFICATIONS

2 – 8 GHz 12-Way Power Divider/Combiner	
Model Number	DB0208
Frequency Range	2 – 8 GHz
Insertion Loss	1.60 dB Typ., 1.90 dB Max.
Isolation	20 dB Typ., 17 dB Min.
Input VSWR	1.45:1 Typ., 1.55:1 Max.
Output VSWR	1.20:1 Typ., 1.30:1 Max.
Amplitude Balance	$\pm 0.15$ dB Typ., $\pm 0.30$ dB Max.
Phase Balance	$\pm 2.5^\circ$ Typ., $\pm 5.0^\circ$ Max.
Power Handling as Divider	50 W CW Max.
Impedance	50 $\Omega$
Connector Type	SMA Female (other connector available on request)



Design to meet the following environmental specifications:  
(verification optional)

1. Operating Temp: -55°C to +85°C
2. Storage Temp: -65°C to +125°C
3. Shock: MIL-STD-202F, M213, Cond B
4. Altitude: MIL-STD-202F, M105, Cond B
5. Vibration: MIL-STD-202F, M204, Cond B
6. Thermal Shock: MIL-STD-202F, M107, Cond A
7. Temp. Cycle: MIL-STD-202F, M105C, Cond D
8. Humidity: MIL-STD-202F, M103, Cond B  
(Optional with Hysol epoxy seal)

#### Standard Finishing

Housing: Rugged Conductive Aluminum Housing  
Connector Housing: Passivated Stainless Steel  
Connector Center PIN: Beryllium copper, Gold plated

#### Note:

1. Insertion loss refers to the sum of the output power to the input power
2. Standard connector is SMA female for all the ports
3. Other connector combination is available on request
4. Power handling is under the condition that all the outputs are connected to the loads with 1.20:1 or better VSWR and the unit is mounted with excellent heat sink